

OPTICAL DEVICE

Michael D. GOLDSTEIN, Avi YARON and Shay GHILAI

IND 17

FIELD OF THE INVENTION

5 The present invention relates to endoscopes, microscopes and boroscopes, in general and to stereoscopic image pick up devices with color imaging capability, in particular.

BACKGROUND OF THE INVENTION

10 Stereoscopic image detection devices are known in the art. Such devices are required to obtain and provide a combination of small cross section and high image quality. It will be appreciated by those skilled in the art that high image quality, in general, is characterized by stereoscopic vision accuracy, color capabilities, high resolution and illumination
15 requirements.

 It is noted that conventional methods, which provide stereoscopic images, require a wider optical path than a monocular one. Such a widened optical path enlarges the cross-section required for the detection device considerably. Hence, the requirement for a small cross
20 section is not maintained.

SUB 17 ~~US Patent No. 5,527,263 to Jurgen, is directed to a dual optical path stereo endoscope with simple optical adjustment. US Patent No. 5,776,049 to Takahashi, is directed to a "Stereo Endoscope in Stereo Endoscope Imaging Apparatus" and provides a device which utilizes a
25 combination of two optical paths with two CCD units, capable of variable zoom.~~

 Auto-stereoscopic devices, which utilize one optical system to provide a stereo effect, are also known in the art. Such a device is provided in US patent No. 5,603,687 to Hori, which is directed to a device
30 with two parallel optical axes and two CCD elements. Hori selected an

asymmetrical approach, wherein one optical channel a large aperture for light and details, and the other optical channel provides a parallax image for stereoscopic imagery to the proximal CCD.

US patent No. 5,613,936 to Czarnek, is directed to a stereoscopic endoscope device which utilizes light polarization and time multiplexing, in order to transmit each different polarized image corresponding to left and right images multiplexed in time, through one optical channel that transfers images from the lateral side of the endoscope shaft. This endoscope has to be inserted deeper into the human cavity to receive a stereo image. It must also be used with a head mounted display device called "switched shutter glasses" that causes eye irritation. It is noted that according to Czarnek each image is received in 25% of original quality. As much as 50% of the light received from the object, is lost due to polarization considerations and as much as 50% of the remaining information is lost due to channel switching.

Sub B27 US patent No. 5,588,948, to Susumu, is directed to a stereoscopic endoscope. The stereo effect is produced by having a dividing pupil shutter, which splits the optical path onto the left and right sides, and the up and down sides. These sides are alternately projected on a proximal image pick up device, using time multiplexing. According to another aspect of this reference a distal CCD is included, which is divided to left and right sides with a shading member separating them, for achieving space multiplexing.

U.S. patent No. 5,743,847 to Nakamura et al., is directed to a "Stereoscopic Endoscope Having Image Transmitting Optical-System and Pupil Dividing Unit that are Axially Movable With Respect to Each Other"; which uses a plural pupil dividing means and one optical channel. U.S. patent No. 5,751,341 to Chaleki et al, is directed to a "Stereoscopic Endoscope System", which is basically a two channel endoscope, with one

or two proximal image sensors. A rigid sheath with an angled distal tip could be attached to its edge and be rotated, for full view.

U.S. Patent No. 5,800,341 to McKenna et al., is directed to an "Electronically Steerable Endoscope", which provides different fields of view, without having to move the endoscope, using a plurality of CCD cells and processing means. U.S. Patent No. 5,825,534 to Strahle, is directed to a "Stereo Endoscope having a Folded Sideline Sight Line" including stereo-endoscope optical channel, having a sight line folded relative to tube axis.

U.S. Patent No. 5,828,487 to Greening et al., is directed to a "Stereoscopic Viewing System Using a Two Dimensional Lens System" which in general, provides an alternative R-L switching system. This system uses a laterally moving opaque leaf, between the endoscope and the camera, thus using one imaging system. US patent No. 5,594,497 to Ahern, describes a distal color CCD, for monocular view in an elongated tube.

The above descriptions provide examples of auto-stereoscopic inventions, using different switching techniques (Time division multiplexing) and polarization of channels or pupil divisions (spatial multiplexing), all in an elongated shaft. When color image pick up devices are used within these systems, the system suffers from reduced resolution, loss of time related information or a widened cross section.

The issue of color imagery or the issue of a shaft-less endoscope is not embedded into any solution.

To offer higher flexibility and to reduce mechanical and optical constraints it is desired to advance the image pick-up device to the frontal part of the endoscope. This allows much higher articulation and lends itself easily to a flexible endoscope. Having a frontal pick up device compromises the resolution of the color device due to size constraints (at this time).

SUMMARY OF THE PRESENT INVENTION

It is an object of the present invention to provide a novel system for stereoscopic imaging using a lenticular lens layer and a sensor array, and a novel method for operating the same, which overcomes the disadvantages of the prior art.

In accordance with the present invention, there is thus provided a stereoscopic device, which includes a lenticular lens layer and a color light sensor array. The lenticular lens layer includes a plurality of lenticular elements. Each of the lenticular elements is located in front of a selected group of the light sensors of the sensor array, thereby directing light from different directions to different light sensors within the selected group of the light sensors.

In accordance with a further aspect of the invention, there is provided a stereoscopic device, which includes a lenticular lens layer and a light sensor array, including a plurality of light sensors, where each of the light sensors detects light at a predetermined range of wavelengths.

The stereoscopic device according to the invention can be constructed as a large-scale device, such as a television camera or a small-scale device such as an endoscope.

In a stereoscopic device according to the invention, each of the lenticular elements includes light directing means, which distinguish between at least two directions of light. For example, each of the lenticular elements can be shaped in a general semi-cylindrical shape. Each of the lenticular elements can alternatively include light directing means, which distinguish between four directions of light. For example, such a lenticular element can be shaped in a general semispherical shape.

According to one aspect of the invention, each of the selected groups of the light sensors includes an even number of light sensors. According to another aspect of the invention, each of the selected groups of the light sensors includes an odd number of light sensors.

image in a stereoscopic manner. The produced image can be partially stereoscopic.

The predetermined ranges of wavelengths, which are applicable for the light sensors as well as for the illumination light beams can be selected from the list consisting of substantially visible red color light, substantially visible green color light, substantially visible blue color light, substantially visible cyan color light, substantially visible yellow color light, substantially visible magenta color light, substantially infra-red light, substantially ultra-violet light, visible light, and the like.

For example, either the light sensor array or the light beams can include a color combination of red-green-blue (RGB), cyan-yellow-magenta-green (CYMG), a white light color combination and the like.

In accordance with a further aspect of the invention, there is thus provided a method for detecting a stereoscopic image. The method includes the steps of splitting light which arrives from different directions, using a lenticular lens layer, thereby producing at least two images, which are intertwined in a master image, and detecting the master image.

The method can further include the step of reconstructing each of the images from the master image. In addition, the method can further include the step of displaying the images using a stereoscopic display device.

Furthermore, the method can include the step of simultaneously displaying the images on a stereoscopic display device. In addition, the method can further include the steps of sequentially illuminating a detected area with alternating beams of light, of different ranges of wavelength, and associating the master image in time, with the currently illuminating ranges of wavelength.

The step of reconstructing can include the steps of determining a range of wavelengths for each pixel within each one of the images, and determining

an intensity level for each pixel within each one of the images. The step of reconstructing can further include the steps of selecting one of the pixels, associated with a predetermined range of wavelengths, determining the pixels associated with another range of wavelengths, in the vicinity of the selected pixel, calculating an approximated level of the other range of wavelengths at the location of the selected pixel, and starting again from the step of selecting.

In accordance with another aspect of the present invention, there is thus provided a stereoscopic device for detecting a stereoscopic image.

The stereoscopic device includes at least two apertures, a multi wavelength light sensor array and a controllable multi wavelength illumination unit. Each aperture includes a plurality of light valves. The controllable multi wavelength illumination unit produces at least two alternating beams of light, where each beam of light is characterized as being in a different range of wavelengths. Each light valve is operative to open at a different predetermined timing. Furthermore, the multi wavelength light sensor array detects a plurality of images, where each of the images corresponds to a predetermined combination of an open state of a selected light valve and a selected mode.

In accordance with a further aspect of the present invention, there is thus provided a method for detecting a stereoscopic image. The method includes the steps of alternating between at least two apertures, producing a sequence of at least two illumination beams and detecting a plurality of frames. The apertures are directed at an object. The illumination beams are produced in different ranges of wavelengths. Each of the frames is detected for a combination, which includes a selected aperture and a selected illumination beam.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the drawings in which:

5 Figure 1 is a schematic illustration of a three dimensional object and a stereoscopic vision apparatus, constructed and operative in accordance with a preferred embodiment of the present invention;

 Figure 2 is a schematic illustration of a stereoscopic vision apparatus, constructed and operative in accordance with another preferred
10 embodiment of the present invention;

 Figure 3A is a schematic illustration of a super-pixel, constructed and operative in accordance with a further preferred embodiment of the present invention;

 Figure 3B is a schematic illustration of the super-pixel of Figure
15 3A and a lenticular element, constructed and operative in accordance with a another preferred embodiment of the present invention;

 Figure 3C is a schematic illustration of a sensor array and a lenticular lens layer, constructed and operative in accordance with a further preferred embodiment of the present invention;

20 Figure 4 is a schematic illustration of a super-pixel, constructed and operative in accordance with another preferred embodiment of the present invention;

 Figure 5A is a schematic illustration of a color super-pixel, constructed and operative in accordance with a further preferred
25 embodiment of the present invention;

 Figure 5B is a schematic illustration of the color super-pixel of Figure 5A, with a single lenticular element, constructed and operative in accordance with another preferred embodiment of the present invention;

 Figure 5C is a schematic illustration of the color super-pixel of
30 Figure 5A, combined with three lenticular elements, constructed and

operative in accordance with a further preferred embodiment of the present invention;

Figure 6 is a schematic illustration of a sensor array and a lenticular lens layer, constructed and operative in accordance with another preferred embodiment of the present invention;

Figure 7A is a schematic illustration of method for operating the apparatus of Figure 2, operative in accordance with a further preferred embodiment of the present invention;

Figure 7B is an illustration in detail of a step of the method of Figure 7A;

Figure 7C is a schematic illustration of a sensor array and a lenticular lens layer constructed and operative in accordance with another preferred embodiment of the present invention;

Figure 8 is a schematic illustration of a stereoscopic vision apparatus, constructed and operative in accordance with a further preferred embodiment of the present invention;

Figure 9A is a view in perspective of a section of light sensors, and a lenticular element, constructed and operative in accordance with another preferred embodiment of the present invention;

Figure 9B is a view from the bottom of the lenticular element and the section of light sensors of Figure 9A;

Figure 9C is a view from the side of the lenticular element and the section of light sensors of Figure 9A;

Figure 10 is a view in perspective of a section of light sensors, and a lenticular element, constructed and operative in accordance with a further preferred embodiment of the present invention;

Figure 11 is a view in perspective of a sensor array and a lenticular layer, constructed and operative in accordance with another preferred embodiment of the present invention;

Figure 12A is a schematic illustration of a detection apparatus, constructed and operative in accordance with a further preferred embodiment of the present invention;

Figure 12B is another schematic illustration of the detection apparatus of Figure 12A;

Figure 13 is a schematic illustration of a detection apparatus, constructed and operative in accordance with another preferred embodiment of the present invention;

Figure 14A is a partially schematic partially perspective illustration of a combined illumination and detection device, constructed and operative in accordance with a further preferred embodiment of the present invention;

Figure 14B is a partially schematic partially perspective illustration of the combined illumination and detection device of Figure 14A, a controller and output frames, constructed and operative in accordance with another preferred embodiment of the present invention;

Figure 15 is an illustration in perspective of a color illumination unit, constructed and operative in accordance with a further preferred embodiment of the present invention;

Figure 16 is a view in perspective of a sensor array and a partial lenticular layer, constructed and operative in accordance with another preferred embodiment of the present invention;

Figure 17 is a view in perspective of a sensor array and a partial lenticular layer, constructed and operative in accordance with a further preferred embodiment of the present invention;

Figure 18 is a schematic illustration of a sensor array and a partial lenticular layer, constructed and operative in accordance with another preferred embodiment of the present invention;

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention overcomes the disadvantages of the prior art by providing a continuous vision stereoscopic apparatus, using a generally lenticular lens layer, a light sensor array and an image processing system.

Reference is now made to Figure 1, which is a schematic illustration of a three dimensional object and a stereoscopic vision apparatus, generally referenced 100 constructed and operative in accordance with a preferred embodiment of the present invention. Apparatus 100 includes a lenticular lens layer 104, a light sensor array 102, a processor 106 and two display devices 108R and 108L. Apparatus 100 is placed in front of a three-dimensional object 150. An optical assembly 152 is placed between apparatus 100 and object 150, for focusing the image of object 150 on light sensor array 102.

Light sensor array 102 includes a plurality of sensors 110, 111, 112, 113, 114, 115, 116, 117, 118 and 119. Lenticular lens layer 104 includes a plurality of lenticular elements 130, 132, 134, 136 and 138. Each one of the lenticular elements is located above two light sensors, in a way that lenticular element 130 is located above sensors 110 and 111, lenticular element 132 is located above sensors 112 and 113, lenticular element 134 is located above sensors 114 and 115, lenticular element 136 is located above sensors 116 and 117 and lenticular element 138 is located above sensors 118 and 119.

The light sensors 110, 111, 112, 113, 114, 115, 116, 117, 118, and 119, detect light as directed by the lenticular lens elements 130, 132, 134, 136 and 138, and provide respective information to the processor 106. The processor 106 processes this information, produces a pair of images, as will be explained in detail hereinbelow, and provides them to the display units 108R and 108L, which in turn produce visual representations of these images.

Hence light sensors 110, 112, 114, 116 and 118 detect the left side image of object 150, while light sensors 111, 113, 115, 117 and 119 detect the right side image of object 150. The light sensor array 102 provides data relating to the detected light intensity at each of the light sensors to the processor 106.

The processor processes this data, produces a right side image from the data relating to the right side image and a left side image from the data relating to the left side, and provides the respective image to the respective display unit 108R and 108L. In the present example, the processor 106 utilizes the data received from sensors 110, 112, 114, 116 and 118 to determine the data provided to pixels 144A, 144B, 144C, 144D and 144E. Similarly, the processor 106 utilizes the data received from sensors 111, 113, 115, 117 and 119 to determine the data which is to be provided to pixels 142A, 142B, 142C, 142D and 142E.

According to the present invention, the right side image and the left side image are detected at the same time and hence, can also be displayed at the same time. According to another aspect of the present invention, each of the light sensors 110, 111, 112, 113, 114, 115, 116, 117, 118, and 119, includes a plurality of color sensing elements, which together cover a predetermined spectrum, as will be described in detail herein below.

Reference is now made to Figure 2, which is a schematic illustration of a stereoscopic vision apparatus, generally referenced 200 constructed and operative in accordance with another preferred embodiment of the present invention. Apparatus 200 includes a sensor assembly 202, an interface 210, a processor 208, a movement detector 230, a light source 206, a memory unit 204, a stereoscopic video generator 212 and a stereoscopic display 214. The sensor assembly 202 is connected to the interface 210 using a flexible cord 218. The interface 210 is connected to processor 208, memory unit 204, and the light source 206. The processor 208 is further connected to the memory unit 204,

movement detector 230 and to the stereoscopic video generator 212. The stereoscopic video generator 212 is further connected to the stereoscopic display 214. Movement detector 230 detects the movement of sensor assembly 202 relative to an object. For this purpose, movement detector 230 is attached to sensor assembly 202. In the case of a rigid endoscope, the movement detector can be attached to any part of the endoscope rod, since the movement of the endoscope head can be determined according to the movement of any point of the endoscope rod.. The operation of system 200, according to data received from movement detector 230, is described herein below.

The sensor assembly 202 includes a focusing element, which in the present example is a lens 226, a lenticular lens layer 222, a light sensor array 220, an interface 228 and a light projecting means 224. The lenticular lens layer 222 is attached to the light sensor array 220. According to the invention, the light sensor array 220 can be any type of sensing array, such as a CCD detector, a CMOS detector, and the like. The light sensor array 220 is connected to the interface 228, which can also act as a supporting base.

The stereoscopic display 214 includes two display units, a left display unit 216L (for placing in front of the left eye of the user) and a right display unit 216R (for placing in front of the right eye of the user). Hence, the stereoscopic display 214 is capable of displaying stereoscopic images continuously. Such a stereoscopic display unit is for example the ProView 50 ST head mounted display, manufactured and sold by Kaiser Electro-Optics Inc., a US registered company, located in Carlsbad, California. Another example for a stereoscopic display unit is the virtual retinal display (VRD) unit, which is provided by MICROVISION Inc., a US registered company, located in Seattle, Washington. It is noted that any method, which is known in the art for displaying stereoscopic, and for that matter three-dimensional images, is applicable for the present invention.

The stereoscopic video generator 212 provides the video signals to the stereoscopic display 214, which in turn produces two images, one using right display unit 216R and another using left display unit 216L.

It is noted that the general size of the sensor assembly 202 is dictated by the size of the sensor array and can be in the order of a few millimeters or a few centimeters. This depends on the size of each of the sensors in the array and the total number of sensors (i.e. the required optical resolution).

According to one aspect of the invention, each of the sensors in light sensor array 220, is a full range sensor, which yields data relating to a gray scale stereoscopic image. According to another aspect of the invention, each of the sensors in the light sensor array, can be adapted so as to provide full color detection capabilities.

Reference is now made to Figure 3A, which is a schematic illustration of a super-pixel, generally referenced 300, constructed and operative in accordance with a further preferred embodiment of the present invention. Super-pixel 300 includes a left section of sensors which includes three sensors 302, 304 and 306, and a right section of sensors which also includes three sensors 308, 310 and 312. Sensors 302 and 310 detect generally red colored light, sensors 304 and 312 detect generally green colored light and sensors 306 and 308 detect generally blue colored light. Hence, each of the sections includes a complete set of sensors for detecting light in the entire visible spectrum.

Reference is further made to Figure 3B, which is a schematic illustration of the super-pixel 300 of Figure 3A and a lenticular element, generally referenced 318 constructed and operative in accordance with a another preferred embodiment of the present invention. The lenticular element 318 is located on top of super-pixel 300, where its right side covers the right section of the super-pixel 300, and its left side covers the left section of the super-pixel 300. Accordingly, the lenticular element 318 directs light, which

arrives from the left (right view image), to the left section of the super-pixel 300, where it is detected in full spectrum by sensors 302, 304 and 306. The data provided by these sensors can later be utilized to reconstruct an image in full color. Similarly, the lenticular element 318 directs light, which
5 arrives from the right (left view image), to the right section of the super-pixel 300, where it is detected in full spectrum by sensors 308, 310 and 312.

Reference is now made to Figure 3C, which is a schematic illustration of a sensor array, generally referenced 330, and a lenticular lens layer,
10 generally referenced 332, constructed and operative in accordance with a further preferred embodiment of the present invention. Sensor array 330 is a matrix of $M \times N$ super-pixels, which are generally referenced 340. For example, the upper left super-pixel is denoted $340_{(1,1)}$, the last super-pixel in the same column is denoted $340_{(1,N)}$ and the lower-right pixel is denoted
15 $340_{(M,N)}$. A lenticular lens layer 332 of which three lenticular elements are shown (referenced 334), is placed over the sensor array 330.

Lenticular element $334_{(1)}$ covers the first column of super-pixels 340 from super-pixel $340_{(1,1)}$ to super-pixel $340_{(1,N)}$. Lenticular element $334_{(2)}$ covers the second column of super-pixels 340 from super-pixel
20 $340_{(2,1)}$ to super-pixel $340_{(2,N)}$. Lenticular element $334_{(3)}$ covers the third column of super-pixels 340 from super-pixel $340_{(3,1)}$ to super-pixel $340_{(3,N)}$. Accordingly, each of the lenticular elements of the lenticular lens layer covers an entire column of super-pixels.

It is noted that a super-pixel according to the present invention
25 can include sensors in any set of colors such as red-green-blue (RGB), cyan-yellow-magenta-green (CYMG), infra-red, ultra-violet and the like, in any arrangement or scheme such as columns, diagonals and the like. It is noted that such a set of colors can be achieved either by using specific color sensitive detectors or by using color filters over the wide spectrum
30 detectors.

Reference is further made to Figure 4, which is a schematic illustration of a super-pixel, generally referenced 350, constructed and operative in accordance with another preferred embodiment of the present invention. Super-pixel 350 includes a left section of sensors which includes four sensors 352, 354, 356 and 358 and a right section of sensors which also includes four sensors 360, 362, 364 and 366. Sensors 352 and 366 detect generally cyan colored light, sensors 354 and 360 detect generally yellow colored light, sensors 356 and 362 detect generally magenta colored light and sensors 358 and 364 detect generally green colored light. Hence, each of the sections includes a complete set of sensors for detecting light in the entire visible spectrum.

Reference is further made to Figures 5A, 5B and 5C. Figure 5A is a schematic illustration of a super-pixel, generally referenced 370, constructed and operative in accordance with a further preferred embodiment of the present invention. Figure 5B is a schematic illustration of super-pixel 370 combined with a single lenticular element, generally referenced 384, constructed and operative in accordance with another preferred embodiment of the present invention. Figure 5C is a schematic illustration of super-pixel 370 combined with three lenticular elements, generally referenced 386, constructed and operative in accordance with a further preferred embodiment of the present invention.

The color arrangement which is provided for super-pixel 370 is typical for vertical light detection arrays, where each column of sensors is coated with light filtering layer of a different color. As can be seen in Figure 5A, super-pixel 370 includes a plurality of light sensors 372, 374, 376, 378, 380 and 382. Light sensors 372 and 378 are blue color range sensors. Light sensors 374 and 380 are green color range sensors. Light sensors 376 and 382 are red color range sensors.

Reference is now made to Figure 6, which is a schematic illustration of a sensor, generally referenced 390, and a lenticular lens

layer, generally referenced 392, constructed and operated in accordance with another preferred embodiment of the present invention. Sensor 390 is logically divided into a plurality of super-pixels, generally referenced 394_(x,y). For example, the upper-left super-pixel is referenced 394_(1,1) and the lower-right side super-pixel is referenced 394_(M,N).

As can be seen from Figure 6, the color arrangement of sensor 390 is diagonal. Hence, each super pixel has a different color arrangement, and generally speaking, there are several types of super-pixels, such as red-blue (super pixel 394_(M-2,N)), green-red (super pixel 394_(M-1,N)) and blue-green (super pixel 394_(M,N)).

Reference is now made to Figure 7A, which is a schematic illustration of a method for operating apparatus 200, operative in accordance with a further preferred embodiment of the present invention. In step 400, the apparatus 200 splits light which arrives from different directions, utilizing the lenticular lens 222. Each of the lenticular elements produces two light sectors, one sector which includes light rays arriving from the left side, and another sector which includes light rays arriving from the right side.

In step 402, the apparatus detects each light sector separately, using a plurality of light detectors, each detecting a portion of its respective sector. With reference to Figure 3B, sensors 302, 304 and 306 detect light which arrives from the lenticular element 318, at the left side sector and sensors 308, 310 and 312 detect light which arrives from the lenticular element 318, at the right side sector. Each of the sensors detects light at a sub-sector.

In step 404, the apparatus 200 determines the light characteristics as detected by each of the light sensors, at each of the sub-sectors. In step 408, the apparatus 200 utilizes the data, which was accumulated from selected sub-sectors to determine and produce an image representing a view from one side. In step 406, the apparatus 200 utilizes the data, which

was accumulated from other selected sub-sectors determine and produce an image representing a view from another side. In step 410, the apparatus 200 displays both images using a continuous stereoscopic display device.

5 According to a further aspect of the invention, information from selected pixels can be used to enhance information for other pixels. For example, color information of pixels, which are associated with a first color is used for extrapolating that color at the location of another pixel, associated with a second color.

10 Reference is further made to Figures 7B and 7C. Figure 7B is an illustration in detail of step 406 of Figure 7A. Figure 7C is a schematic illustration of a sensor array, generally referenced 450, and a lenticular lens layer, generally referenced 452, constructed and operative in accordance with another preferred embodiment of the present invention.

15 Sensor array 450 includes a plurality of pixel sensors, referenced 454, each associated with a selected color. For example, pixel sensors $R_{(1,1)}$, $R_{(2,2)}$, $R_{(3,3)}$, $R_{(4,4)}$, $R_{(1,4)}$ and $R_{(4,1)}$ are associated with the red color. Pixel sensors $G_{(2,1)}$, $G_{(3,2)}$, $G_{(4,3)}$, $G_{(1,3)}$ and $G_{(2,4)}$ are associated with the green color. Pixel sensors $B_{(1,2)}$, $B_{(2,3)}$, $B_{(3,4)}$, $B_{(3,1)}$ and $B_{(4,2)}$ are associated with the blue color.

20

In step 420, the system, according to the invention, selects a pixel sensor, associated with a first color. With reference to Figure 7C, the selected pixel sensor according to the present example is pixel sensor $R_{(3,3)}$.

25 In step 422, the system determines pixels, associated with a second color, in the vicinity of the selected pixel. It is noted that these pixels can also be restricted to ones, which relate to the same image side of the selected pixel. With reference to Figure 7C, the second color is green and the green pixel sensors, in the vicinity of pixel sensor $R_{(3,3)}$,

DDOET-12966960
respective of same image side are pixel sensors $G_{(5,1)}$, $G_{(3,2)}$, $G_{(3,5)}$, $G_{(5,4)}$, and $G_{(1,3)}$.

In step 424, the system calculates an approximation of the level of the green color at the location of the selected pixel $R_{(3,3)}$. It is noted that the calculation can include a plurality of approximation procedures, such as calculating the weighted average level, depending on the location of pixel sensors $G_{(5,1)}$, $G_{(3,2)}$, $G_{(3,5)}$, $G_{(5,4)}$, and $G_{(1,3)}$, with respect to the location of the selected pixel sensor $R_{(3,3)}$. Similarly, blue color level at the location of the selected pixel sensor $R_{(3,3)}$, can be calculated using the information received from pixel sensors $B_{(1,2)}$, $B_{(1,5)}$, $B_{(3,1)}$, $B_{(3,4)}$ and $B_{(5,3)}$. Hence the present invention provides a method for enhancing picture resolution by means of color information interpolation, using image processing.

It is noted that any of the lenticular elements is not necessarily round shaped, but can be formed according to other optical structures which are based on various prism designs and the like, which provide the directing of beams of light coming from different directions to different directions.

Reference is now made to Figure 8, which is a schematic illustration of a stereoscopic vision apparatus, generally referenced 500, constructed and operative in accordance with a further preferred embodiment of the present invention. Apparatus 500 includes a sensor assembly 502, a frame grabber 510, a processor 508, a light source 506, a memory unit 504, a stereoscopic video generator 512 and a stereoscopic display 514. The sensor assembly 502 is connected to the frame grabber 510 using a flexible cord 518. The frame grabber 510, the processor 508, the memory unit 504 and the stereoscopic video generator 512 are all interconnected using a common bus.

The sensor assembly 502 is generally similar to the sensor assembly 202, described herein above in conjunction with Figure 2. The

sensor assembly 502 includes a lens 526, a lenticular lens layer 522, a light sensor array 520, an analog to digital converter (A/D) 528 and light projecting means 524. The lenticular lens layer 522 is attached to the light sensor array 520. Light sensor array 520 is connected to the A/D 528; which could also act as a supporting base. The light projecting means 524 is connected to light source 506, which provides light thereto.

The stereoscopic display 514 includes two display units, a left display unit 516L (for placing in front of the left eye of the user), and right display unit 516R (for placing in front of the right eye of the user). Hence, the stereoscopic display 514 is capable of displaying stereoscopic images continuously.

The sensor assembly 502 operates in a manner, similar to that of sensor assembly 202, described hereinabove in conjunction with Figure 2. An electronic representation of this information, is provided by the A/D converter 528, after being converted into digital format.

The information data is received by the frame grabber 510 and hence made available to the processor 508 via the bus. As the processor 508 processes the information, it uses the memory unit 504 as temporary storage. After processing the information, the processor 508 produces two matrixes each being a reconstructed representation relating to one of the originally detected images. The processor 508 provides these matrixes to the stereoscopic video generator 512, which in turn produces two respective video signals, one for the left view image and another for the right view image. The stereoscopic video generator 512 provides the video signals to the stereoscopic display 514, which in turn produces two images, one using right display unit 516R and another using left display unit 516L.

Reference is now made to Figures 9A, 9B and 9C. Figure 9A is a view in perspective of a super-pixel, generally referenced 550, and a lenticular element, generally referenced 552, constructed and operative in

accordance with another preferred embodiment of the present invention. Figure 9B is a view from the bottom of the lenticular element 552 and the super-pixel 550 of Figure 9A. Figure 9C is a view from the side of the lenticular element 552 and the super-pixel 550 of Figure 9A.

5 The super-pixel 550 includes four sensor sections, 554, 556, 558 and 560, arranged in a rectangular formation. The lenticular element 552 is shaped like a dome and is basically divided into four sections, each facing a different one of the sensor sections 554, 556, 558 and 560.

10 The super-pixel 550 and the lenticular element 552 form together, an optical detection unit, which is capable of detecting and distinguishing light which arrives from four different directions. The lenticular element 552 directs a portion of the upper-left side view of the detected object to sensor section 554 and directs a portion of the lower-left side view of the detected object to sensor section 556. In addition, the
15 lenticular element 552 directs a portion of the upper-right side view of the detected object to sensor section 560 and a portion of the lower-right side view of the detected object to sensor section 558.

20 It is noted that according to a further aspect of the invention, the four-direction arrangement, which is described in Figures 9A, 9B and 9C can be used to logically rotate the image which is provided to the user, without physically rotating the device itself. At first, sensor sections 560 and 558 are used to form the right-side image and sensor sections 554 and 556 are used to form the left-side image. A rotation at an angle of 90° clockwise, is provided by assigning sensor sections 554 and 560, to form
25 the right side image, and assigning sensor sections 556 and 558, to form the left-side image. It is further noted that a rotation in any desired angle can also be performed by means of a linear or other combination of sensor sections, when reconstructing the final images.

30 Reference is now made to Figure 10, which is a view in perspective of a section of light sensors, generally referenced 570, and a lenticular

element, generally referenced 572, constructed and operative in accordance with a further preferred embodiment of the present invention. Lenticular element 572 is extended to cover the entire area of the section of pixels, so as to enhance light transmission thereto.

5 Reference is now made to Figure 11, which is a view in perspective of a sensor array, generally referenced 580, and a lenticular layer, generally referenced 582, constructed and operative in accordance with another preferred embodiment of the present invention. The lenticular layer 582 includes a plurality of four direction lenticular elements such as described
10 in Figures 9A and 10. The sensor array 580 is logically divided into a plurality of sensor sections, generally referenced $584_{(x,y)}$. For example, the upper left sensor section is referenced $584_{(1,1)}$ and the lower-right sensor section is referenced $584_{(M,N)}$. Each of the sensor sections is located, beneath a lenticular element and detects light directed thereby.

15 Reference is now made to Figures 12A and 12B. Figure 12A is a schematic illustration of a detection apparatus, generally referenced 600, constructed and operative in accordance with a further preferred embodiment of the present invention. Figure 12B is another schematic illustration of detection apparatus 600, of Figure 12A.

20 Detection apparatus 600 includes an optical assembly 602, a lenticular layer 604 and an array of sensors 608. The detection apparatus 600 detects images of an object 610, which includes a plurality of object sections 610A, 610B, 610C and 610D.

25 Sensor array 608 includes a plurality of super-pixels 608A, 608B, 608C and 608D. Each of these super-pixels is divided into a left-side section and a right-side section. For example, super-pixel 608A includes a left-side section, designated $608A_L$ and a right-side section, designated $608A_R$.

30 The optical assembly 602 is divided into two optical sections 602_L and 602_R , each directed at transferring an image, which represents a

different side. Optical section 602_R transfers an image, which is a view from the right side of object 610. Optical section 602_L transfers an image, which is a view from the left side of object 610.

5 A plurality of light rays 612, 614, 616 and 618 are directed from all sections of the object 610 to the left side of optical assembly 602 (i.e., optical section 602_L), and are directed to the lenticular layer 604. Here, these rays are further directed to the left-side view associated sensor sections, which are sensor sections 608_L (i.e., sensor sections 608A_L, 608B_L, 608C_L and 608D_L).

10 With reference to Figure 12B, a plurality of light rays 622, 624, 626 and 628 are directed from all sections of the object 610 to the right side of optical assembly 602 (i.e., optical section 602_R), and are directed to the lenticular layer 604. Here, these rays are further directed to the right-side view associated sensor sections, which are sensor sections 15 608A_R, 608B_R, 608C_R and 608D_R.

Reference is now made to Figure 13, which is a schematic illustration of a detection apparatus, generally referenced 630, constructed and operative in accordance with another preferred embodiment of the present invention. Detection apparatus 630 includes an optical assembly, 20 which is divided into four sections 632, 634, 636 and 638, a lenticular layer 642 and an array of sensors 640. The detection apparatus 630 detects images of an object 648, which includes a plurality of object sections 648A, 648B, 648C, 648D, 648E and 648F. Light rays, which arrive from object 648 to any of the optical sections, are directed to a lenticular 25 element of the lenticular layer 642, according to their origin.

In the present example, all of the light rays 646A, 646B, 646C and 646D arrive from object element 648A. Each of these rays is received at a different optical section. Ray 646A is received and directed by optical section 636, ray 646B is received and directed by optical section 638, ray 30 646C is received and directed by optical section 634 and ray 646D is

received and directed by optical section 632. Each of the optical sections directs its respective ray to a specific lenticular element 642_(1,1), at the right side of the lenticular layer 642. The location of lenticular element 642_(1,1) is respective of the location of the object element 648. The lenticular element
5 642_(1,1) directs each of the rays to predetermined light sensors within its respective super-pixel 640_(1,1).

In accordance with a further aspect of the present invention, there is provided a reduced size color stereovision detection system, which uses time-multiplexed colored light projections, and respective
10 time-multiplexed frame grabbing.

Reference is now made to Figures 14A and 14B. Figure 14A is a partially schematic, partially perspective illustration of a combined illumination and detection device, generally referenced 650, constructed and operative in accordance with a further preferred embodiment of the
15 present invention. Figure 14B is a partially schematic, partially perspective illustration of the combined illumination and detection device 650 of Figure 14A, a controller, generally designated 662, and output frames, constructed and operative in accordance with another preferred embodiment of the present invention.

Device 650 includes a lenticular layer 652, a full spectrum sensor array 654, an optical assembly 660 and an illuminating unit 656, surrounding the optical assembly 660. Illuminating unit 656 includes a plurality of illuminating elements, generally referenced 658, each being of a specific predetermined color. Illuminating elements 658_{RED} produce
20 generally red light, illuminating elements 658_{GREEN} produce generally green light and illuminating elements 658_{BLUE} produce generally blue light. It is noted that each of the illuminating elements can be of a specific color (i.e., a specific wavelength), a range of colors (i.e., a range of wavelengths) or alternating colors. For example, a multi-color LED.

Each group of illuminating elements, which are of the same color, is activated at a different point in time. For example, illuminating elements 658_{RED} are activated and shut down first, illuminating elements 658_{GREEN} are activated and shut down second and illuminating elements 658_{BLUE} are activated and shut down last. Then the illuminating sequence is repeated.

With reference to Figure 14B, the controller 662 is connected to the sensor array 654 and the illuminating unit 656. The sensor array 654 includes full spectrum sensors, which are capable of detecting red, green and blue light, but cannot indicate the wavelength of the detected light. The controller 662 associates the images, which are detected at any particular moment, using the sensor array 654, with the color of the illuminating elements, which were active at that particular moment.

Hence, the first detected frame 664 in an illumination sequence is considered red, since the illuminating elements which were active at that time, were illuminating elements 658_{RED}. Similarly, the second detected frame 666 in an illumination sequence is considered green, since the illuminating elements, which were active at that time, were illuminating elements 658_{GREEN}. Finally, the last detected frame 668 in an illumination sequence is considered blue, since the illuminating elements, which were active at that time, were illuminating elements 658_{BLUE}. It is noted that any other combination of colors is applicable for this and any other aspect of the present invention, such as CYMG and the like.

Reference is now made to Figure 15, which is an illustration in perspective of a color illumination unit, generally referenced 670, constructed and operative in accordance with a further preferred embodiment of the present invention. Unit 670 includes a light-guiding element 671, which is generally shaped as an open-cut hollow cone, having a narrow section 674 and a wide section 672. A detection head according to the invention, such as described in Figure 2 (referenced 202),

can be placed in the hollow space of the light-guiding element 671. A multi-color light source 680 can be connected to the narrow section 674. Light, such as light ray 678, which is emitted from the light source 680, is directed via the light guiding element 671, and is projected through the wide section 672.

According to a further aspect of the invention, a remote multi-color light source 682 can be connected to the narrow section 674 via additional light guiding members such as optic-fibers 684. Light, such as light ray 676, which is emitted from the light source 682, is directed via the light guiding members 684 to the narrow section 674. The light-guiding element 671 guides ray 676, and projects it through the wide section 672. This arrangement is useful when using an external light source, which is to be placed outside the inspected area (for example, outside the body of the patient).

According to a further aspect of the invention, a full spectrum illumination unit, which produces white light, is combined with a device such as sensor assembly 202 (Figure 2).

Reference is now made to Figure 16, which is a view in perspective of a sensor array, generally referenced 700, and a partial lenticular layer, generally referenced 702, constructed and operative in accordance with another preferred embodiment of the present invention. The partial lenticular layer 700 includes a plurality of four direction lenticular elements such as described in Figures 9A and 10. The sensor array 700 is logically divided into a plurality of sensor sections, generally referenced $704_{(x,y)}$. For example, the upper left sensor section is referenced $704_{(1,1)}$ and the lower-right sensor section is referenced $704_{(M,N)}$. Some of the sensor sections, in the perimeter, are located beneath lenticular elements and others, such as the sensor sections in the center rectangle, which is defined by sensor sections $704_{(4,3)}$ - $704_{(7,6)}$ are not. Accordingly, the sensors which are located at the center rectangle can

not be used to provide multi-direction (stereoscopic or quadrosopic) information. Instead, these sensors provide enhanced resolution monoscopic information.

Reference is now made to Figure 17, which is a view in perspective of a sensor array, generally referenced 720, and a partial lenticular layer, generally referenced 722, constructed and operative in accordance with a further preferred embodiment of the present invention. The partial lenticular layer 720 includes a plurality of four direction lenticular elements such as described in Figures 9A and 10. The sensor array 720 is logically divided into a plurality of sensor sections, generally referenced $724_{(x,y)}$. For example, the upper left sensor section is referenced $724_{(1,1)}$ and the lower-right sensor section is referenced $724_{(M,N)}$. Here, some of the sensor sections, in the center, (such as sensor section $724_{(4,2)}$) are located beneath lenticular elements and others, such as the sensor sections in the perimeter (such as sensor section $724_{(1,1)}$) are not. Accordingly, the sensors which are located at the center provide multi-direction (stereoscopic or quadrosopic) information and the ones in the perimeter provide enhanced resolution monoscopic information.

In accordance with a further aspect of the present invention there is provided a partial lenticular layer, which includes spaced apart lenticular elements. Reference is now made to Figure 18, which is a schematic illustration of a sensor array, generally referenced 740, and a partial lenticular layer, generally referenced 742, constructed and operative in accordance with another preferred embodiment of the present invention.

The partial lenticular layer 742 includes a plurality of lenticular elements designated $744_{(1)}$, $744_{(2)}$ and $744_{(3)}$. Lenticular element $744_{(1)}$ is located over the first two left columns of color sensors, generally designated $746_{(1)}$, of sensor array 740. Hence, the information received from these first two left columns of color sensors of sensor array 740

contains stereoscopic information. The third and fourth columns of color sensors, generally designated 746₍₂₎, of sensor array 740 do not have a lenticular element located thereon, and hence, cannot be used to provide stereoscopic information.

5 Similarly, lenticular elements 744₍₂₎ and 744₍₃₎ are located over color sensors column pairs, 746₍₃₎ and 746₍₅₎, respectively, while color sensors column pairs, 746₍₄₎ and 746₍₆₎ are not covered with lenticular elements.

Reference is now made to Figure 19, which is a schematic
10 illustration of a sensor array, generally referenced 760, and a partial lenticular layer, generally referenced 762, constructed and operative in accordance with another preferred embodiment of the present invention. Lenticular layer 762 includes a plurality of lenticular elements, referenced
15 764₍₁₎, 764₍₂₎, 764₍₃₎ and 764₍₄₎, being of different sizes and located at random locations over the sensor array 740. It is noted that any structure of partial lenticular layer is applicable for the invention, whereas the associated image processing application has to be configured according to the coverage of that specific lenticular layer, and address covered sensors and uncovered sensors appropriately.

20 In accordance with a further aspect of the present invention, there is provided a system, which produces a color stereoscopic image. The structure of the stereoscopic device defines at least two viewing angles, through which the detector can detect an image of an object. According to one aspect of the invention, the stereoscopic device includes
25 an aperture for each viewing angle. Each of the apertures can be opened or shut. The stereoscopic device captures a stereoscopic image, by alternately detecting an image of an object, from each of the viewing angles, (e.g., by opening a different aperture at a time and shutting the rest) through a plurality of apertures, (at least two), each time from a

different apertures. The final stereoscopic image can be constructed from the images captured with respect to the different viewing angles.

The detection of stereoscopic color image is provided by illuminating the object with a sequence of light beams, each at a different wavelength, and detecting a separate image for each wavelength and aperture combination.

Reference is now made to Figures 20A and 20B. Figure 20A is a schematic illustration of a system, generally referenced 800, for producing a color stereoscopic image, in a right side detection mode, constructed and operative in accordance with a further preferred embodiment of the invention. Figure 20B is an illustration of the system of Figure 20A, in a left-side detection mode.

System 800 includes a multiple aperture 804, a controller 834, an image detector 812, a storage unit 836, an image processor 838, a movement detector 814 and an illumination unit 830. The controller 834 is connected to the multiple aperture 804, the image detector 812, the storage unit 836, movement detector 814 and to the illumination unit 830. The storage unit 836 is further connected to the image processor 838. The multiple aperture 804 includes a plurality of apertures, generally referenced 802, where each aperture can be activated to be open or closed. It is noted that when an aperture is open it is at least transparent to a predetermined degree to light, and when an aperture is closed, it substantially prevents the travel of light therethrough. Any type of controllable light valve can be used to construct each of the apertures. Movement detector 814 detects the movement of image detector 812. The detected movement can be a linear displacement, an angular displacement, and the derivatives thereof such as velocity, acceleration, and the like. The operation of system 800, according to data received from movement detector 814, is described herein below in connection with Figures 25A, 25B, 25C, 26A, 26B and 26C.

Light valve elements are components, which have an ability to influence light in at least one way. Some of these ways are, for example: scattering, converging, diverging, absorbing, imposing a polarization pattern, influencing a polarization pattern which, for example, may be by rotation of a polarization plane, influencing wave length, diverting a beam's direction for example by using digital micro-mirror display (also known as DMD) or by using field effect, influencing phase, interference techniques, which either blocks or transfers a portion of beam of light and the like. Activation of light valve elements, which are utilized by the present invention, can be performed either electrically, magnetically or optically. Commonly used light valve elements are liquid crystal based elements, which either rotate or create and enforce a predetermined polarization axis.

In the present example, multiple aperture 804 includes two apertures 802_R and 802_L. The controller 834 further activates the multiple aperture 804, so as to alternately open apertures 802_R and 802_L. In Figure 20A, aperture 802_R is open while aperture 802_L is closed and in Figure 20B, aperture 802_R is closed while aperture 802_L is open.

Light rays, which reflect from various sections of the object 810, pass through the currently open aperture (802_R in Figure 20A and 802_L in Figure 20B). Thereby, light rays 822 and 824 arrive from section 810A of object 810, pass through aperture 802_R, and are detected by detection element 808A, while light rays 826 and 828 arrive from section 810D, pass through aperture 802_R and are detected by detection element 808D. Hence, when aperture 802_R is open, then the system 800 provides a right side view of the object 810.

With reference to Figure 20B, when aperture 802_L is open, light rays 827 and 825 arrive from section 810A, pass through aperture 802_L, and are detected by detection element 808A, while light rays 821 and 823 arrive from section 810D, pass through aperture 802_L, and are detected by

detection element 808D. Thereby, the system 800 provides a left side view of the object 810.

The illumination unit 830 is a multi-color illumination unit, which can produce light at a plurality of wavelengths. The controller 834 provides a sequence of illumination commands to the illumination unit 830, so as to produce a beam at a different predetermined wavelength, at each given moment. In the present example, the illumination unit is a red-green-blue (RGB) unit, which can produce a red light beam, a green light beam and a blue light beam. It is noted that illumination unit 830 can be replaced with any other multi-color illumination unit, which can produce either visible light, non-visible light or both, at any desired wavelength combination (CYMK and the like).

Furthermore, illumination unit 830 can be a passive unit, where it receives external commands to move from one wavelength to another, or it can be an active unit, which changes wavelength independently and provides an indication of the currently active wavelength to an external controller. Illumination unit 830 of the present example is a passive unit, which enhances the versatility of the system 800, by providing any wavelength sequence on demand.

The image detector 812 includes a plurality of detection elements 808A, 808B, 808C and 808D. In accordance with one aspect of the invention, detector 812 is a full range color detector, where each of the detection elements is operative to detect light in a plurality of wavelengths. In accordance with another aspect of the invention, the detector 812 is a color segmented detector, where the detection elements are divided into groups, each operative to detect light in a different range of wavelengths. One conventional type of such detectors includes a full range detection array, which is covered by a color filter layer, where each detection element is covered by a different color filter. Accordingly, some of the

detection elements are covered with red filters, others are covered with green filters and the rest are covered with blue filters.

The present invention enhances the color resolution of systems, using such color detectors. It will be appreciated by those skilled in the art that a color segment detector of poor quality may exhibit a wavelength (color) overlap between the different detection elements. For example, when the filters are of poor quality, their filtering functions tend to overlap such that the red filter also passes a small amount of either green or blue light. Hence, the detection element behind the red filter, also detects that small amount of green or blue light, but provides an output measurement as a measurement of red light. Hence, the color detector produces an image, which includes incorrect measurements of red light (e.g. more than the actual red light, which arrived at the detector) as result of that overlap. Accordingly, received information of the inspected object is not valid.

In the present invention, the illumination unit 830 produces a sequence of non-overlapping illumination beams at predetermined wavelengths (i.e., red, blue and green). As explained above, the color detector detects an image, which includes incorrect measurements, as a result of the wavelength (color) filtering overlap. Since the illumination unit 830 and the image acquisition process are synchronized, the imaging system can process each of the acquired images, according to the actual light beam color, which was produced therewith. For example, the illumination unit 830 produces blue light illumination beam. At the same time the color detector detects an image, which also includes actual light measurements in detection elements, which are covered with green and red filters, due to the wavelength overlap. The imaging system can discard light measurements, which are received from detection elements, covered with color filters, which are not blue (e.g., red and green).

Such sequenced color illumination of the object, provides enhanced color resolution, for color image detectors of poor quality, and

obtains the various color images of the inspected object. System 800 can further include a stereoscopic display unit (not shown), connected to controller 834 for displaying a stereoscopic image of object 810. Reference is now made to Figure 21A, which is a schematic illustration of a timing sequence, in which controller 834 (Figure 20A) synchronizes the operation of illumination unit 830, apertures 802_L and 802_R, and image detector 812. Signal 840 represents the timing sequence of the left aperture 802_L. Signal 842 represents the timing sequence of the right aperture 802_R. Signal 844 represents the timing sequence of the blue light beam, produced by the illumination unit 830. Signal 846 represents the timing sequence of the green light beam, produced by the illumination unit 830. Signal 848 represents the timing sequence of the red light beam, produced by the illumination unit 830. Signal 841 represents the timing sequence of the image detector 812, where each image is downloaded therefrom.

Timing sequence 841 rises every time any of the rises of sequences 844, 846 and 848 intersect with a rise of either sequence 842 or sequence 840. For example, rise 841_A indicates a frame download of a blue light – right aperture combination, rise 841_B indicates a frame download of a green light – right aperture combination, and rise 841_C indicates a frame download of a red light – right aperture combination. Similarly, rise 841_D indicates a frame download of a blue light – left aperture combination, rise 841_E indicates a frame download of a green light – left aperture combination and rise 841_F indicates a frame download of a red light – left aperture combination.

It is noted that for some light sources, the produced light beams do not cover the full range of visible light. For such light sources, the missing color components can be reconstructed (interpolated) taking into consideration the physiological assumption, that color reflection response as a function of reflected angle, does not change much with angle.

Reference is further made to Figure 22, which is a schematic illustration of a method for operating system 800 of Figure 20A and 20B, operative in accordance with another preferred embodiment of the present invention. In step 870, a sequence of illumination beams at predetermined wave-lengths is produced. With reference to Figures 20A and 20B, controller 834 provides a sequence of illumination commands to the illumination unit 830, which in turn produces different wavelength light beams, generally referenced 832, at predetermined points in time, towards an object, generally referenced 810.

In step 872 right and left apertures are alternated. Light rays, which reflect from various sections of the object 810, pass through the currently open aperture (802_R in Figure 20A and 802_L in Figure 20B). With reference to Figures 20A and 20B, controller 834 provides a sequence of operating commands to the apertures 802_L and 802_R.

In step 874, a plurality of frames, each for a selected aperture and wavelength combination is detected. Controller 834 operates the image detector so as to detect a plurality of frames, each respective of a selected aperture and wavelength combination.

Light rays 822 and 824 (Figure 20A) arrive from section 810A of object 810, pass through aperture 802_R, and are detected by detection element 808A, while light rays 826 and 828 arrive from section 810D, pass through aperture 802_R and are detected by detection element 808D. It is noted that in the present example, an imaging element (not shown) is introduced in the vicinity of multiple aperture 804. Hence, when aperture 802_R is open, then the system 800 provides a right side view of the object 810.

Light rays 827 and 825 (Figure 20B) arrive from section 810A, pass through aperture 802_L and are detected by detection element 808A, while light rays 821 and 823 arrive from section 810D, pass through aperture 802_L and are detected by detection element 808D. Hence, when

aperture 802_L is open, then the system 800 provides a left side view of the object 810.

With reference to Figure 21A, rise 841_A provides a right side blue image (reference 806^R_B of Figure 20A), rise 841_B provides a right side green image (reference 806^R_G of Figure 20A), and rise 841_C provides a right side red image (reference 806^R_R of Figure 20A). Similarly, rise 841_D provides a left side blue image (reference 806^L_B of Figure 20B), rise 841_E provides a left side green image (reference 806^L_G of Figure 20B), and rise 841_F provides a left side red image (reference 806^L_R of Figure 20B). With reference to Figures 20A and 20B, image detector 812 detects the plurality of frames, and provides right and left output video for image processing.

In step 876 a stereoscopic color image from the plurality of frames, according to their aperture origin is produced. With reference to Figure 20A and Figure 20B, the controller 834 stores the detected images in storage unit 836. Image processor 838 retrieves the detected images from the storage unit 836, and constructs color stereoscopic images.

Hence, the present invention provides an additional way for detecting a color stereoscopic image, using a single image detector for both sides and all colors.

Reference is further made to Figure 21B, which is a schematic illustration of another timing sequence, in which controller 834 (Figure 20A) synchronizes the operation of illumination unit 830, apertures 802_L and 802_R, and image detector 812. Signal 840' represents the timing sequence of the left aperture 802_L. Signal 842' represents the timing sequence of the right aperture 802_R. Signal 844' represents the timing sequence of the blue light beam, produced by the illumination unit 830. Signal 846' represents the timing sequence of the green light beam, produced by the illumination unit 830. Signal 848' represents the timing sequence of the red light beam, produced by the illumination unit 830.

Signal 841' represents the timing sequence of the image detector 812, where each image is downloaded therefrom.

Timing sequence 841' rises every time any of the rises of sequences 844', 846' and 848' intersects with a rise of either sequence 842' or sequence 840'. For example, rise 841'_A indicates a frame download of a blue light – right aperture combination, rise 841'_B indicates a frame download of a blue light – left aperture combination and rise 841'_C indicates a frame download of a green light – right aperture combination. Similarly, rise 841'_D indicates a frame download of a green light – left aperture combination, rise 841'_E indicates a frame download of a red light – right aperture combination and rise 841'_F indicates a frame download of a blue light – left aperture combination.

Reference is now made to Figure 23, which is a schematic illustration of a timing scheme, for operating system 800 of Figures 20A and 20B, in accordance with a further preferred embodiment of the present invention. Signal 850 represents the timing sequence of the left aperture 802_L. Signal 852 represents the timing sequence of the right aperture 802_R. Signal 854 represents the timing sequence of the blue light beam. Signal 856 represents the timing sequence of the green light beam. Signal 858 represents the timing sequence of the red light beam. Signal 851 represents the timing sequence of the image detector 812, where each image is downloaded therefrom. As can be seen in Figure 23, the timing scheme is asymmetric, where the green light beam is activated for a time period which is twice the time period of either the red light beam or the blue light beam. Signal 851 corresponds to this arrangement and provides a green image download rise (references 851_B and 851_E), after a time period which is twice as long with comparison to red image download rises (references 851_C and 851_F) or blue image download rises (references 851_A and 851_D).

Reference is now made to Figure 24, which is a schematic illustration of a timing scheme, for operating system 800 of Figures 20A and 20B, in accordance with another preferred embodiment of the present invention. Signal 860 represents the timing sequence of the left aperture 802_L. Signal 862 represents the timing sequence of the right aperture 802_R. Signal 864 represents the timing sequence of the magenta light beam. Signal 866 represents the timing sequence of the yellow light beam. Signal 868 represents the timing sequence of the cyan light beam. As can be seen in Figure 24, the timing scheme addresses an alternate wavelength scheme and is also asymmetric.

It is noted that a mechanical multi-wavelength illumination unit such as described in the prior art, can be used for implementing the present invention. However, such a system significantly reduces the capability of the user to control illumination duration, wavelength ratio and detection timing, such as described herein above.

It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described here in above. Rather the scope of the present invention is defined only by the claims which follow.